



EN 60598 LED A+++ IK08 IP66 CE

OP01

Product description

- Corrosion resistant aluminum body
- Excellent heat dissipation for cooling electronics components
- Stainless steel screws
- Waterproof and durable silicone gaskets
- Chromate coating
- Electrostatic polyester powder coating
- Anchorage unit with galvanized
- Mechanical impact resistance IK08
- Protection grade IP66
- Electrical installation Class I

Lamp & Optics

- Modo Module®
- Up to 140 lm/w
- 3000k-4000k-6500k
- 220-240v 50-60hz
- Beam angle: 30°, 60°, 90°, 150°
- Cri > 80
- Options : DALI controllable

Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

| Power (W) | A | B | C | Anchor |
|-----------|------|-----|-----|--------|
| 24 | 3000 | 150 | 150 | 4xM12 |
| 36 | 3500 | 150 | 150 | 4xM14 |
| 36 | 4000 | 150 | 150 | 4xM14 |
| 36 | 4500 | 178 | 178 | 4xM16 |
| 42 | 5000 | 178 | 178 | 4xM16 |
| 42 | 6000 | 200 | 200 | 4xM18 |

We reserve the right to make technical changes without prior notice.

www.lightou.com