



EN 60598 LED A+++ IK08 IP66 CE

## OP02

### Product description

Corrosion resistant aluminum body  
 Excellent heat dissipation for cooling electronics components  
 Stainless steel screws  
 Waterproof and durable silicone gaskets  
 Chromate coating  
 Electrostatic polyester powder coating  
 Anchorage unit with galvanized  
 Mechanical impact resistance IK08  
 Protection grade IP66  
 Electrical installation Class I

### Lamp & Optics

Poly Module ®  
 Up to 140 lm/w  
 3000k-4000k-6500k  
 220-240v 50-60hz  
 Beam angle: 30°, 60°, 90°, 150°  
 Cri > 80  
 Options : DALI controllable

### Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

Power (W)	A	B	C	Anchor
20	2000	240	100	4xM12
24	2500	240	100	4xM12
28	3000	240	100	4xM12
36	4000	280	100	4xM14
42	5000	280	100	4xM16
56	6000	300	150	4xM16

We reserve the right to make technical changes without prior notice.

[www.lightou.com](http://www.lightou.com)